

产品编号 (Item No) : NYHP-7300MW

Very Low Loss & Low Z-axis CTE

特点:

- 低介电常数(Dk 3.0@10GHz)
- 介质损耗(Df 0.0014@10GHz)
- Tg >200℃ 高耐热性
- 优异通孔可靠性及 PCB 加工性
- 低吸水性

FEATURES:

- Low Dk (Dk 3.0@10GHz)
- Low Df (Df 0.0014@10GHz)
- Tg >200℃ and high thermostability
- Superior PTH reliability and easy PCB processing
- Low moisture absorption

应用领域:

- 毫米波/汽车雷达应用

APPLICATIONS:

- Millimeter Wave / Automotive Radar

NYHP-7300MW 基板产品规格表 Specification Sheet for Laminate

NYHP-7300MW 覆铜板 NYHP-7300MW Laminate	单位Units	典型值 Typical Value	条件 Condition	测试方法 Test Method
	Metric(English)	1.524mm CCL		IPC-TM-650
1. 抗剥强度 Peel Strength, As received	N/mm(lb/inch)	>0.7 (4.0)	1oz HVLP	2.4.8
2. 体积电阻 Volume Resistivity, 恒温恒湿C-96/35/90	MΩ-cm, Minimum	4×10 ⁸	COND A	2.5.17.1
3. 表面电阻 Surface Resistivity, 恒温恒湿C-96/35/90	MΩ, minimum	2.1×10 ⁸	COND A	2.5.17.1
4. 吸水率 Moisture Absorption	% maximum	0.14		2.6.2.1
5. 介电常数 Permittivity (Laminate & Prepreg as laminated)	Maximum	3.0 ± 0.05	10 GHz/23℃	2.5.5.5
6. 介质损耗 Loss Tangent (Laminate & Prepreg as laminated)	Maximum	0.0014	10 GHz/23℃	2.5.5.5
7. TCDK	PPM/℃	25	-50℃-150℃	2.5.5.5
8. 弯曲强度 Flexural Strength, A. 纵向 Length direction B. 横向 Cross direction	N/mm ² , minimum	210 155	RT	ASTM D790
9. 热应力冲击 Thermal Stress A. 未蚀刻 Unetched B. 蚀刻 Etched	10 sec at 288℃	Pass Pass	288℃	2.4.13.1
10. 燃烧性 Flammability (Laminate & Prepreg as laminated)	Rating	V-0		UL94 (UL File: E213990)
11. 玻璃态转化温度 Glass Transition Temperature	℃	>200	DMA	2.4.24
12. 热分解温度 Decomposition Temperature	℃	410		TD (5% wt loss)
13. 膨胀系数Z-Axis CTE	α1	50		2.4.24
	α2	300		
14. 耐热性(除去铜箔) Thermal Resistance (Copper removed) A.T260 B.T288 C.T300	Minutes Minutes Minutes	>120 > 60 > 60		2.4.24.1
15. 耐CAF性能 CAF Resistance	Pass/Fail	Pass	AABUS	2.6.25

*AABUS = 供需双方商定 As agreed upon between user and supplier.

板材厚度与公差 The thickness & Tolerance

型号 (Model)	厚度 Thickness (mm)	厚度 Thickness (inch)	公差 Tolerance (mm)
NYHP-7300MW	0.127	0.005	±0.025
	0.254	0.010	±0.038
	0.508	0.020	±0.050

板材尺寸 Standard Size

型号 (Model)	英寸/inch	毫米/mm
NYHP-7300MW	36×48	914×1219
	42×48	1067×1219

注：可以根据客户要求的尺寸开 PNL 出货。

Remark: Other size could be available upon request.

铜箔 Copper Foil

型号 (Model)	HVLP3
NYHP-7300MW	Hoz
	1oz

注：Other copper spec could be available upon request