

产品编号: NYHP-7350

High Frequency Very Low Loss Laminate

特点:

- 低介电常数(Dk 3.50@10 GHz)
- 介质损耗(Df 0.0029@10 GHz)
- 无铅兼容板材
- 优异通孔可靠性及 PCB 加工性
- 低吸水性

应用领域:

- 功放/天线
- LNA/LNB

FEATURES:

- Low Dk (Dk 3.50@10 GHz)
- Low Df (Df 0.0029@10 GHz)
- Lead-free compatible
- Superior PTH reliability and easy PCB processing
- Low moisture absorption

- 汽车雷达
- 微波/无线通

NYHP-7350 基板产品规格表 Specification Sheet for Laminate

NYHP-7350 覆铜板 NYHP-7350 Type Laminate	单位Units	典型值 Typical Value	条件 Condition	测试方法 Test Method
	Metric(English)	1.524mm CCL		IPC TM 650
1. 抗剥强度 Peel Strength, As received	N/mm(lb/inch),	0.8 (4.5)	1oz HTE	2.4.8
2. 体积电阻 Volume Resistivity,	MΩ-cm, Minimum	1.0×10 ¹⁰	COND A	2.5.17.1
3. 表面电阻 Surface Resistivity,	MΩ, Minimum	5.1×10 ⁹	COND A	2.5.17.1
4. 吸水率 Moisture Absorption	% maximum	0.13		2.6.2.1
5. 介电常数 Permittivity (Laminate & Prepreg as laminated)	--- maximum	3.50	10 GHz/23℃	2.5.5.5
6. 介质损耗 Loss Tangent (Laminate & Prepreg as laminated)	--- maximum	0.0029	10 GHz/23℃	2.5.5.5
7. TCDK	PPM/℃	40	-50℃-150℃	2.5.5.5
8. 弯曲强度 Flexural Strength, A. 纵向 Length direction B. 横向 Cross direction	N/mm ² , minimum	220 140	RT	2.4.4
9. 热应力冲击 Thermal Stress A. 未蚀刻 Unetched B. 蚀刻 Etched	10 sec at 288℃	Pass Pass	288℃	2.4.13.1
10. 燃烧性 Flammability (Laminate & Prepreg as laminated)	rating	V-0		UL94 (UL File: E213990)
11. 玻璃态转化温度 Glass Transition Temperature	℃	190	DMA	2.4.24
12. 热分解温度 Decomposition Temperature	℃	400		TD (5% wt loss)
13. CTE膨胀系数	X/Y-axis (50~125℃)	PPM/℃	22/25	TMA
	Z-axis	PPM/℃	100	TMA
14. 耐热性(除去铜箔) Thermal Resistance (Copper removed) A.T260 B.T288 C.T300	Minutes Minutes Minutes	>120 > 60 > 60		2.4.24.1
15. PIM		dBc	<-158	AABUS
16. 导热系数 Thermal Conductivity	W/m•℃	0.60		800/1800/2600 MHz ASTM D5470

*AABUS = 供需双方商定 As agreed upon between user and supplier.

板材厚度与公差 The thickness & Tolerance

型号 (Model)	厚度 Thickness (mm)	厚度 Thickness (inch)	公差 Tolerance (mm)
NYHP-7350	0.254	0.01	±0.020
	0.508	0.02	±0.038
	0.762	0.03	±0.050
	1.524	0.06	±0.075

板材尺寸 Standard Size

型号 (Model)	英寸/inch	毫米/mm
NYHP-7350	36×48	914×1219
	42×48	1067×1219

注：可以根据客户要求的尺寸开 PNL 出货。

Remark: Other size could be available upon request.

铜箔 Copper Foil

型号 (Model)	功放	天线/微波/雷达/无线通讯
	HTE	RTF
NYHP-7350	Hoz	Hoz
	1oz	1oz

注：Other copper spec could be available upon request